

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: May

With process factor valid for finished cold rolled and hardened and tempered strip products

Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

Alleima	GRADE		ALLOY & ENERGY SURCHARGE PER KG										
	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD
Alloyed non-stainless steels and carbon steels													
20C	1.1274	1095	1870	9,19	0,82	0,72	0,88	116,93	1,20	6,08	0,81	0,40	0,54
20C2			2258	9,89	0,88	0,77	0,95	125,81	1,29	6,54	0,87	0,43	0,59
10C16Mo3V1				24,97	2,22	1,95	2,40	317,59	3,26	16,52	2,20	1,09	1,48
Sanprint XP				23,47	2,08	1,83	2,26	298,47	3,06	15,52	2,06	1,02	1,39

Martensitic stainless chromium steels													
6C27	1.4007	420	2234	16,96	1,50	1,32	1,63	216	2,21	11,22	1,49	0,74	1,00
7C27Mo2				24,93	2,21	1,94	2,40	317	3,25	16,49	2,19	1,09	1,48
Hiflex				24,93	2,21	1,94	2,40	317	3,25	16,49	2,19	1,09	1,48
Freeflex				25,88	2,30	2,02	2,49	329	3,38	17,12	2,27	1,13	1,53
10C28MO2				25,22	2,24	1,97	2,43	321	3,29	16,68	2,22	1,10	1,49
12C27M				17,42	1,55	1,36	1,68	222	2,27	11,53	1,53	0,76	1,03
12C27				16,88	1,50	1,32	1,62	215	2,20	11,16	1,48	0,74	1,00
14C28N				17,14	1,52	1,34	1,65	218	2,24	11,34	1,51	0,75	1,01
13C26			14141	16,53	1,47	1,29	1,59	210	2,16	10,93	1,45	0,72	0,98
Damax				20,90	1,85	1,63	2,01	266	2,73	13,83	1,84	0,91	1,24
19C27				16,88	1,50	1,32	1,62	215	2,20	11,16	1,48	0,74	1,00

Austenitic stainless steels													
12R11	1.4310	301	2331	39,74	3,53	3,10	3,82	505	5,19	26,29	3,49	1,73	2,35
11R51	1.4310	301	2231	44,97	3,99	3,51	4,33	572	5,87	29,75	3,95	1,96	2,66
13RM19	EN 1.4369			40,32	3,58	3,14	3,88	513	5,26	26,67	3,54	1,76	2,39
316LVM	1,4441	316LVM		82,22	7,29	6,41	7,91	1 046	10,73	54,39	7,23	3,59	4,87
2RK65HV				122,15	10,84	9,52	11,75	1 553	15,94	80,80	10,74	5,33	7,23
3X8R65				64,76	5,75	5,05	6,23	824	8,45	42,84	5,69	2,83	3,83
3R60F1				79,87	7,09	6,23	7,68	1 016	10,43	52,84	7,02	3,49	4,73

Precipitation hardenable steels													
9RU10	1.4568	631	2388	40,23	3,57	3,14	3,87	512	5,25	26,61	3,54	1,76	2,38
NANOFLEX				75,94	6,74	5,92	7,30	966	9,91	50,23	6,67	3,31	4,50
1RK95				39,71	3,52	3,10	3,82	505	5,18	26,27	3,49	1,73	2,35

Duplex stainless steels (austenitic-ferritic)													
SAF2205	EN 1.4462		2377	63,36	5,62	4,94	6,10	806	8,27	41,92	5,57	2,76	3,75
SAF2507	EN 1.4410		2328	73,81	6,55	5,75	7,10	939	9,63	48,82	6,49	3,22	4,37
SAF3207HD				74,21	6,58	5,78	7,14	944	9,69	49,09	6,52	3,24	4,39

Ferritic stainless chromium steel													
1C429				22,65	2,01	1,77	2,18	288	2,96	14,98	1,99	0,99	1,34
1C44Mo20				29,83	2,65	2,33	2,87	379	3,89	19,73	2,62	1,30	1,77
0XC34				18,90	1,68	1,47	1,82	240	2,47	12,50	1,66	0,82	1,12
1C34				18,78	1,67	1,46	1,81	239	2,45	12,42	1,65	0,82	1,11

Nickel-base alloy													
SANICRO75X2	UNS N07750			223,92	19,87	17,45	21,54	2 848	29,23	148,12	19,68	9,77	13,26
SAN62TiNb				195,36	17,33	15,23	18,79	2 484	25,50	129,23	17,17	8,52	11,57

Energy surcharge per kg included in total surcharge				3,96	0,35	0,31	0,38	50	0,52	2,62	0,35	0,17	0,23