

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: March

With process factor valid for finished cold rolled and hardened and tempered strip products
Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

GRADE			ALLOY & ENERGY SURCHARGE PER KG											
Alleima	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD	BRL
<i>Alloyed non-stainless steels and carbon steels</i>														
20C	1.1274	1095	1870	6,63	0,58	0,49	0,60	93	0,87	4,39	0,55	0,27	0,39	3,55
20C2			2258	7,02	0,61	0,52	0,64	99	0,92	4,64	0,58	0,29	0,42	3,75
10C16Mo3V1				18,98	1,66	1,39	1,73	267	2,48	12,56	1,57	0,78	1,13	10,14
Sanprint XP				18,42	1,61	1,35	1,68	259	2,41	12,19	1,52	0,76	1,09	9,85

<i>Martensitic stainless chromium steels</i>														
6C27	1.4007	420	2234	10,88	0,95	0,80	0,99	153	1,42	7,20	0,90	0,45	0,65	5,81
7C27Mo2				17,89	1,57	1,31	1,63	251	2,34	11,84	1,48	0,74	1,06	9,56
Hiflex				17,89	1,57	1,31	1,63	251	2,34	11,84	1,48	0,74	1,06	9,56
Freeflex				18,80	1,65	1,38	1,71	264	2,46	12,44	1,55	0,78	1,11	10,05
10C28MO2				18,04	1,58	1,32	1,64	254	2,36	11,94	1,49	0,74	1,07	9,65
12C27M				11,13	0,98	0,82	1,01	156	1,45	7,37	0,92	0,46	0,66	5,95
12C27				10,83	0,95	0,80	0,98	152	1,42	7,17	0,89	0,45	0,64	5,79
14C28N				10,97	0,96	0,81	1,00	154	1,43	7,26	0,91	0,45	0,65	5,86
13C26			14141	10,64	0,93	0,78	0,97	150	1,39	7,04	0,88	0,44	0,63	5,69
Damax				14,36	1,26	1,05	1,31	202	1,88	9,50	1,19	0,59	0,85	7,68
19C27				10,83	0,95	0,80	0,98	152	1,42	7,17	0,89	0,45	0,64	5,79

<i>Austenitic stainless steels</i>														
12R11	1.4310	301	2331	24,87	2,18	1,83	2,26	349	3,25	16,46	2,05	1,03	1,47	13,29
11R51	1.4310	301	2231	29,59	2,59	2,17	2,69	416	3,87	19,58	2,44	1,22	1,75	15,82
13RM19	EN 1.4369			25,16	2,21	1,85	2,29	354	3,29	16,65	2,08	1,04	1,49	13,45
3X22R60HV	1,4441	316LVM		56,98	4,99	4,18	5,18	801	7,45	37,72	4,71	2,35	3,38	30,46
2RK65HV				84,30	7,39	6,19	7,67	1 185	11,02	55,79	6,96	3,48	5,00	45,07
3X8R65				44,71	3,92	3,28	4,07	628	5,85	29,59	3,69	1,84	2,65	23,90
3R60F1				55,06	4,83	4,04	5,01	774	7,20	36,44	4,55	2,27	3,27	29,44

<i>Precipitation hardenable steels</i>														
9RU10	1.4568	631	2388	25,18	2,21	1,85	2,29	354	3,29	16,67	2,08	1,04	1,49	13,46
NANOFLEX				56,77	4,98	4,17	5,16	798	7,42	37,57	4,69	2,34	3,37	30,35
1RK95				25,08	2,20	1,84	2,28	353	3,28	16,60	2,07	1,03	1,49	13,41

<i>Duplex stainless steels (austenitic-ferritic)</i>														
SAF2205	EN 1.4462		2377	45,90	4,02	3,37	4,17	645	6,00	30,38	3,79	1,89	2,72	24,54
SAF2507	EN 1.4410		2328	53,50	4,69	3,93	4,86	752	6,99	35,41	4,42	2,21	3,17	28,60
SAF3207HD				52,59	4,61	3,86	4,78	739	6,88	34,81	4,35	2,17	3,12	28,12

<i>Ferritic stainless chromium steel</i>														
1C429				13,98	1,23	1,03	1,27	196	1,83	9,25	1,15	0,58	0,83	7,47
1C44Mo20				20,56	1,80	1,51	1,87	289	2,69	13,61	1,70	0,85	1,22	10,99
0XC34				11,93	1,05	0,88	1,08	168	1,56	7,90	0,99	0,49	0,71	6,38
1C34				11,87	1,04	0,87	1,08	167	1,55	7,86	0,98	0,49	0,70	6,34

<i>Nickel-base alloy</i>														
SANICRO75X2	UNS N07750			139,21	12,20	10,22	12,66	1 957	18,20	92,14	11,50	5,74	8,26	74,42
SAN62TiNb				121,49	10,65	8,92	11,05	1 707	15,88	80,41	10,04	5,01	7,21	64,95

<i>Energy surcharge per kg included in total surcharge</i>				2,85	0,25	0,21	0,26	40	0,37	1,88	0,24	0,12	0,17	1,52